### Modelling injection with structured clouds

### **Matthew Goodson and Fabian Heitsch**

Dept. of Physics and Astronomy, University of North Carolina at Chapel Hill mgoodson@unc.edu

Short-lived radioisotopes, such as Aluminum-26 ( $\tau_{1/2} \approx 0.7 \text{ Myr}$ ), were present and active in the early Solar System<sup>1</sup>. The origin and incorporation mechanism of the SLRs is still debated<sup>2,3</sup>.

External enrichment scenarios via supernovae or stellar winds encounter a common bottleneck: failure to inject enough material into our natal molecular cloud<sup>3</sup>. There is an inevitable impedance mismatch between the hot diffuse ejecta and the cold dense cloud.

Most simulations assume a spherical cloud geometry. However, observations reveal that molecular clouds are structured on all scales. Further, a smooth surface deflects incident ejecta and inhibits mixing. We suggest that sub-structure in the target cloud will increase injection efficiencies.





Figure 1. A clumpy geometry is more realistic and could capture more impinging material.

We use the **Athena code**<sup>4</sup> to solve the ideal hydrodynamics equations on a fixed grid in 2-D. We employ a weak ( $\gamma = 1.1$ ) adiabatic equation of state, and self-gravity is included via an open-boundary FFT solver.

A shocked wind of hot gas propagates from the left boundary and impacts a dense molecular cloud. We model **structured clouds with random clumps**. We trace the ejecta with a passive scalar field.


After 1 crossing time, we measure the fraction of ejecta that has been incorporated into collapsing cloud regions, i.e. regions of enhanced density and converging flow. Various cloud masses, "filling factors", and shock Mach numbers are explored.

Our test case is a 25,000  $\rm M_{\odot}$  cloud of radius ~9 pc, in thermal equilibrium with an ambient medium of 7500 K and 1 cm $^3$  (Cs ~ 8.3 km s $^{-1}$ ).



**Figure 2.** Snapshots of number density (top) and passive tracer (bottom) in our fiducial 2-D simulation: Mach 5 shock, 50% full cloud,  $1024^2$  resolution. The shock propagates from the left.  $t_{\rm c}$  is the shock crossing time (2.5 Myr in this instance).

#### Sub-structure increases the injection efficiency in most cases.



**Table 1.** Results for our standard test case in 2-D, at a resolution of 1024<sup>2</sup>. f, is evaluated after one shock crossing time.

<b>Figure 3.</b> Injection efficiencies (f <sub>i</sub> )
for smooth and structured clouds in
2-D, as a function of crossing time
(t <sub>c</sub> ). 5 random structured
distributions are sampled. We
report the median and standard
deviation. The resolution is 1024 <sup>2</sup> .

Mach #	Filling Factor	$f_i(t = t_c)$	$f_i/f_{i,100}$
	25%	0.09	$3.2 \times 10^{5}$
2.5	50%	0.08	$2.9 \times 10^{5}$
	75%	0.03	$1.1 \times 10^{5}$
	100%	$2.80 \times 10^{-7}$	1.0
	25%	0.17	2.1
5.0	50%	0.21	2.6
	75%	0.22	2.8
	100%	0.08	1.0
	25%	0.17	2.1
7.5	50%	0.19	2.4
	75%	0.23	2.9
	100%	0.08	1.0
	25%	0.14	1.4
10.0	50%	0.17	1.7
	75%	0.21	2.1
	100%	0.1	1.0

## Sub-structure has the largest effect at low Mach numbers.




Figure 4. Injection efficiency vs. cloud filling factor, evaluated at  $t=t_c$ .

Resolution is  $1024^2$ .


Mach 2.5.

Mach 2.6.

Mach 7.5.

Mach 10

# Resolution controls our turbulent mixing.



**Figure 5.** Resolution convergence test.  $f_i$  evaluated at  $t = t_c$ . We do not use mesh refinement.

Clumpy sub-structure is not only more realistic -- it may help resolve the SLR injection problem. The increase in injection efficiency is usually a factor of 2-3, but at slightly supersonic ejecta speeds the increase can be several orders of magnitude. A clumpy cloud surface allows incident material to penetrate to greater depths rather than being deflected on impact. The increased surface area also produces more turbulent mixing, which incorporates the SLRs into dense regions.

However, **our turbulence is resolution-dependent**. We will need mesh refinement to better resolve the mixing scales, as well as sub-grid turbulence models to control resolution effects. Future simulations will also include improved thermal physics, magnetic fields, and star formation via sink particles.

1.000 Mach 5

0.100 Smooth (100%) Structured (50%)

0.001 0.0 0.2 0.4 0.6 0.8 1.0 1.2 t / t<sub>c</sub>

**Figure 6.** Preliminary results in 3-D show similar results to 2-D. Resolution is 1024<sup>3</sup>. Gravitational collapse terminates the simulations. Further time evolution will require mesh refinement and sink particles.



Supported by NSF Grant AST-1109085 and NC Space Grant

[1] Lee, T., Papanastassiou, D. A., & Wasserburg, G. J. 1976, Geophys. Rev. Lett., 3, 41

[2] Adams, F. C. 2010, ARAA, 48, 47

[3] Boss, A. P. & Keiser, S. A. 2013, ApJ, 770, 51

[4] Stone, J. M. et al. 2008, ApJS, 178, 137





